

CONTINUOUS BAND SEALER






High Production
Output



Secured Sealing



Easy to use



Optional Gas Flushing



Consistent Quality



International Standards

A Continuous Band Sealer Machine is a versatile packaging solution designed to seal bags and pouches with precision and speed. It operates continuously, ensuring high efficiency for sealing tasks in industries like food, pharmaceuticals, and electronics. With adjustable temperature controls and durable construction, it provides reliable, airtight seals for enhanced product safety and shelf life.

It features Continuous, efficient, and adjustable sealing with durable build for various pouch types.

Continuous Band Sealer is Used for sealing food, pharmaceutical, electronics, and agricultural product packaging.



Easy to Operate

Designed with simplicity, our machine features an intuitive smart interface and straightforward controls, ensuring easy operation for all experience levels.

Easy Maintenanse

With a focus on convenience, our machine is engineered for easy maintenance, featuring accessible components and straightforward service procedures.

Rapid Tech Support

Benefit from our 24*7 rapid tech support, offering prompt assistance and solutions to minimize downtime and keep your machine running smoothly.

Both can be equipped with an optional Gas Flushing Attachment.

CONTINUOUS BAND SEALER (HORIZONTAL ARRANGEMENT)

CONTINUOUS BAND SEALER (VERTICAL ARRANGEMENT)





TECHNICAL SPECIFICATIONS

Model	<u>Horizontal Type</u>	Model	<u>Vertical Type</u>
Power	650 W (220 V AC)	Power	650 W (220 V AC)
Sealing Speed	0 To 12 m / min	Sealing Speed	0 To 12 m / min
Sealing Width	8 To 10 mm	Sealing Width	8 To 12 mm
Temperature Range	0 To 300` C	Temperature Range	0 То 300' С
Conveyor Size (L x W)	840 x 153 mm	Conveyor Size (L x W)	840 x 153 mm
Conveyor Loading	5 kg	Conveyor Loading	15 kg
Overall Dimension (L x W x H)	840 x 380 x 320 mm	Overall Dimension (L x W x H)	840 x 380 x 600
Max. Pouch Length	14 Inch	Max. Pouch Length	18 Inch

^{*}The above mentioned values are indicative and can be modified at any time at the discretion of the company.